



AARON No.22 Cineast

High End Stereo & 6 channel pre-amplifier

Technical Specifications:

Output signal max:	7V eff.
Distortion THD:	0.0064% 1V / 1Khz
Distortion TIM:	0.0041% 1V / 50Hz/7Khz 4:1
Hum and Noise level:	-107dB ref: Max, output level
Bandwidth:	5hz - 100Khz -3dB
Input impedance:	47K Ω
Output impedance:	1 Ω I max.= 30mA
Gain:	3x = 10db
Slew rate	28V/uS
AC voltage:	115VAC / 230VAC internal switch 50/60Hz
+/-10% Power consumption:	Idle 2VA - Operation 5 VA
Volume control:	64 step Log digital controlled ladder switch
Features:	Each input channel programmable - input gain (-16dB) Each output channel programmable output gain (-16dB) Programmable switch 2channel to 4 channel mode Programmable switch 2 channel with sub out mode in/out, Infrared remote control
Inputs:	2x6channel + 6x2channel line input RCA gold plated
Outputs:	6channel line out + 2channel rec out RCA gold plated
Controls:	2x rotary encoder with push button
Dimensions:	440x108x375mm WxHxD

Engineered and manufactured



with pride in Europe

WEEE Registration:
DE 70986408



© 2007